

## **DtiCorp.com Is Introducing 5 Honeywell P658 Pneumatic Switches**

*Honeywell P658 are pneumatic-electric switches (P658A,B,E and F) used to convert a pneumatic signal from a controller to an electrical switching action (SPDT) to provide start and stop control of equipment such as fans and pumps. Replacement devices available for Johnson, Powers, Robertshaw, Barber-Colman, and older Honeywell pneumatic/ electric switches.*

October 13, 2010 (FPRC) -- Popular Honeywell online retailer DtiCorp.com (<http://www.DtiCorp.com>) is introducing 5 brand new Honeywell P658 Pneumatic Switches. Honeywell P658 are pneumatic-electric switches (P658A,B,E and F) used to convert a pneumatic signal from a controller to an electrical switching action (SPDT) to provide start and stop control of equipment such as fans and pumps. Replacement devices available for Johnson, Powers, Robertshaw, Barber-Colman, and older Honeywell pneumatic/ electric switches.

The Honeywell P658A, B, C, E, and F Pneumatic/Electric Switches convert a pneumatic signal from a controller or other pneumatic device to a spdt electric switch action. The P658A, B, E, and F are used for on/off control of fans and pumps, energizing electric heaters, day-night control of unitary equipment, interlock functions, and control of other electrical equipment commonly found in mechanical systems. The P658C is intended for use with DeltaNet Systems or any system requiring lowimpedance switching for monitoring status.

### Features:

- Models available for surface or panel mounting.
- Barb protected by open cage.
- All ferrous parts plated to prevent corrosion.
- Factory calibrated setpoint field adjustable to meet job requirements.
- Neoprene diaphragm element.

### Specifications:

- Operating Temperature Range:
  - P658A, C: -20 to 140F (-4 to 60C)
  - P658B: -20 to 160F (-4 to 71C)
  - P658E, F: 40 to 140F (4 to 60C)
- Operating Humidity Range: 5 to 95% rh; 80F (27C) maximum wet-bulb temperature
- Finish:
  - P658A: Gray-beige cover
  - P658B, C, E, and F: Gray; plated ferrous parts
- Optional Accessory:
  - CCT2363 5/8–18 Hex Nut (for internal-enclosure mounting that extends barb outside of enclosure)
- Agency Listings:
  - P658A: UL Listing, Category SDYF; intended for direct separate installation in the field, CSA

Listing,

Volume II.

P658B: UL File No. E49725, Category SDFY2, Component Listing

P658E, F: UL File No. E49725, Category SDFY2, Component Listing, CSA Listing, Volume I

P658C: UL Listing not applicable (low-voltage application)

Models available:

1. P658A1013 Surface Mounted Pneumatic / Electric Switch with Factory Calibrated at 10 psi.
2. P658B1012 Panel Mounted Pneumatic / Electric Switch. Factory Calibrated at 10 psi.
3. P658E1001 Panel Mounted Pneumatic / Electric Switch. No Factory Calibration.
4. P658E1167 Panel Mounted Pneumatic / Electric Switch. No Factory Calibration.
5. P658F1000 Panel Mounted Pneumatic / Electric Switch. No Factory Calibration.

About Us: DtiCorp.Com (<http://www.DtiCorp.com>) carries more than 35,000 HVAC products, including industrial, commercial and residential parts and equipment from Honeywell, Johnson Contols, Robertshaw, Jandy, Grundfos, Armstrong and more. Our online catalog is easy to navigate and search, and all products have a picture and a description. If a customer has any questions about a product, they can call 800-757-5999 and speak with one of our product experts. Our mission is to offer the best prices anywhere to our customers.

Julian Arhire

Manager DtiCorp.com

Phone: 954.484.2929

Fax: 954.206.0767

Web: <http://www.DtiCorp.com>

###

### **Contact Information**

For more information contact Julian Arhire of DtiCorp.com (<http://dticorp.com>)

954.484.2929

### **Keywords**

[Popular Honeywell online retailer](#)

[Electric Switches](#)

[Pneumatic Switches](#)

You can read this press release online [here](#)